

LA-UR-21-25404

Approved for public release; distribution is unlimited.

Title: Nuclear Materials Production & Technical Nuclear Forensics

Author(s): Scott, Mark Robert

Intended for: Virtual presentation to the University of Texas

Issued: 2021-06-09



Nuclear Materials Production & Technical Nuclear Forensics

Intelligence & Systems Analysis Group (A-2)




Mark Scott


2021



Fundamentals of a Nuclear Fission Chain Reaction



Demon Core



Critical Mass


Isotope	Bare Sphere Critical Mass	IAEA Significant Quantity (SQ)
235	52 kg	25 kg
²³⁹ Pu	10 kg	8 kg

Absorbed

Pathways to a Nuclear Weapon

To create a nuclear weapon you must first obtain weapons grade material.

- Enriched uranium
- Plutonium




Hurdles to Manufacturing an Improvised Nuclear Device (IND)


What is the primary hurdle to manufacturing an IND?

Obtaining Weapon-Usable Nuclear Material (WUNM)

- First Line of Defense (FLD):
 - Securing WUNM at civilian and defense facilities against theft and/or diversion.
- Second Line of Defense (SLD):
 - Building radiation detection capacity in partner countries to enhance border control to deter, detect and interdict WUNM.
- International Nonproliferation Export Control Program (INECP)
 - To prevent the illicit procurement of equipment, materials, and technological know-how to develop weapons of mass destruction (WMD).


Uranium Isotopes






U-235	Acronym	Description
<0.7	DU	Depleted U
0.7	NU	Natural U
0.7 - 20	LEU	Low Enriched U
>20	HEU	Highly Enriched U
>90		Weapons Grade

Enriched-U Production




Uranium Enrichment Techniques

Gas Centrifuge




Gaseous Diffusion




Uranium Enrichment

Aerodynamic Nozzle




Laser Enrichment AVLIS, MLIS, SILEX



Alternative Methods

- Chemical (CHEMEX)
- **Plasma**
- Thermal (Oak Ridge)

EMIS or Calutron




Comparison of Gaseous Diffusion & Centrifuge

Gaseous Diffusion



- High pressure High thru-put
- Operates as Single Cascade
- 1000 stages: natural → 3.5% 4000 stages; natural \rightarrow 90%
- 100-300 sq. ft. per stage
- ~ 2,500 kW hr/SWU
- Extract 25x more energy out

Centrifuge



- Low pressure Low thru-put
- **Multiple Cascades**
- 10's- 100 stages: natural → 3.5% 300 - 1000 stages: natural → 90%
- 6-8 sq. ft. per stage
- < 50 kW hr/SWU
- Extract 1500x more energy out


Visualizing U-235 Enrichment

U-238 Atoms


U-235 Atoms

Feed	Product	Centrifuges*
0.7%	20%	96
20%	90%	15

^{*40} SWU/year per centrifuge




Centrifuges to Produce HEU from LEU Centrifuges to produce 100kg of product per year



A Westinghouse 1,000 MWe PWR reactor has a core load of 66,410 kg of uranium fuel between 2.1% - 3.1% U-235

Uranium Isotopes



Production:


U-239
$$\beta \longrightarrow Np-239$$

Np-239
$$\beta \longrightarrow Pu-239$$

Conversion:

$$Pu-239 + n \longrightarrow Pu-240$$


238[] -> 239PU -> 240PU




Pu-240 %	<1976 >1976		
<7	Weapons Grade		
7-19	Dogator Crado	Fuel Grade	
>19	Reactor Grade	Reactor Grade	

(Significant Quantity of Pu-239: 8kg)


Plutonium Production



U-235 Neutron Fission X-Section




Moderation of Fast Neutrons



On average water (H₂O) will moderate a neutron after 16 collisions.

Heavy water (D₂O) requires approximately 29 collisions to moderate a neutron.



Hydrogen isotope diagram from NASA JPL

Classes of Reactors

Reactor Class	Moderator	Coolant	Fuel
Light Water (PWR, BWR, VVER)	Water	Water	LEU
Heavy Water (CANDU, PHWR)	Heavy Water	Water	Natural
Graphite (gas) (MAGNOX, AGR)	Graphite	CO ₂	Natural
Graphite (water) (RBMK, Hanford)	Graphite	Water	LEU/Nat.

Other Reactor Types: TRIGA, PBR, Fast, SMR, MSR, AHR

PWR at Cape Town, SA



Pic: Koeberg nuclear power station, Cape Town, South Africa. Credit: Bjorn Rudner

RBMK at Ignalina, LT



CANDU at Bruce Power




Photo: Bruce Power/Cameco Corp.

Pu Production – Rules of Thumb

Typical production rate:


0.91 g-Pu/MWd - Graphite Reactor1.2 g-Pu/MWd - Heavy Water Reactor

Reactor Type	% U-235 Fuel	Typical Burnup (GWd/MTU)	Pu / MTU	% Pu-240
Graphite	0.7%	1.2 - 6.0	1.1 – 3.3 kg	3.8 – 28%
CANDU	0.7%	5 – 10	3.0 - 4.5 kg	21 – 31%
PWR	1.5% - 5.0%	15 – 60	5.6 – 13 kg	13 – 26%
BWR	1.1% - 3.5%	10 – 60	4.0 – 12.5 kg	11 – 31%
TRIGA	20%*	80 – 130	8.5 – 12 kg**	14 – 19%
TRIGA	93%*	80 – 130	1.5 – 2.2 kg**	5 – 7.5%


^{*} TRIGA enrichment is 20, 70 and 93%

^{**}TRIGA core load is around 2.5 kg of U-235


Nuclear Reactor Fuel to Separated Plutonium



Sample Collection




Forensic Process for Spent Fuel




Nuclide Production as a Burnup Indicator





Fuel Age or Cooling Time



Los Alamos National Laboratory

Employees: 13,137

Students: 1,323 Post docs: 498



- 65% male, 35% female
- 45% minorities
- 67% university degrees
- 27% undergraduate degrees
- 19% master's degrees
- 21% PhD



Questions